

57000 SERIES TRAFFIC ARROWS

FLEET



Control Box & Cable Options (sold separately)



77501







Main Power Cable

To be used with 77504 20' - 77271 30' - 77272 40' - 77273


10' - 77270

Rated Switch Box

77504 Outdoor

Features

- The hermetically sealed light-head will not be affected by outside factors such as temperature, humidity & condensation
- NO DOWN TIME heads are field replaceable in less than one minute!
- SWS pressure clip system ensure that no special tools are ever required
- A choice of control platforms cab-mounted slim-line control box or NEW outdoor rated switch box
- All electrical connections are made using the industry known and trusted DTM series connections from TE
- Adapter kit available for use on existing wire installations (77280)
- Stop-Turn lighting kits available (96050)
- 5 Year Warranty (Control box 1 Year Warranty)




57000 SERIES TRAFFIC ARROWS

FLEET



Dimensions



Available Colors

* All part numbers listed are amber color. Contact factory for custom requests

Part #	Vdc	Amps	# of Modules in Shaft	# of Modules per Arm	Flash Patterns	Length	Height
57724-1	12	1.8A	4	1	7	27"	12.5"
57730-1	12	1.8A	5	1	7	32.75"	12.5"
57730-2	12	2.4A	5	2	7	32.75"	22"
57736-1	12	2.1A	6	1	7	38.5"	12.5"
57736-2	12	2.7A	6	2	7	38.5"	22"
57736-3	12	3.3A	6	3	7	38.5"	30.5"
57742-1	12	2.4A	7	1	7	44.25"	12.5"
57742-2	12	3.0A	7	2	7	44.25"	22"
57742-3	12	3.6A	7	3	7	44.25"	30.5"
57748-1	12	2.7A	8	1	7	50"	12.5"
57748-2	12	3.3A	8	2	7	50"	22"
57748-3	12	3.9A	8	3	7	50"	30.5"
57754-1	12	3.0A	9	1	7	55.75"	12.5"
57754-2	12	3.6A	9	2	7	55.75"	22"
57754-3	12	4.2A	9	3	7	55.75"	30.5"
57760-1	12	3.3A	10	1	7	61.5"	12.5"
57760-2	12	3.9A	10	2	7	61.5"	22"
57760-3	12	4.5A	10	3	7	61.5"	30.5"
57766-1	12	3.3A	11	1	7	67.25"	12.5"
57766-2	12	3.9A	11	2	7	67.25"	22"
57766-3	12	4.5A	11	3	7	67.25"	30.5"
57772-1	12	3.6A	12	1	7	73"	12.5"
57772-2	12	4.2A	12	2	7	73"	22"
57772-3	12	4.8A	12	3	7	73"	30.5"

✓ = Top Seller

57000 SERIES SPLIT TRAFFIC ARROWS



- The hermetically sealed light-head will not be affected by outside factors such as temperature, humidity & condensation
- NO DOWN TIME heads are field replaceable in less than one minute!
- SWS pressure clip system ensure that no special tools are ever required
- A choice of control platforms cab-mounted slim-line control box or NEW outdoor rated switch box
- All electrical connections are made using the industry known, and trusted DTM series connections from TE
- Adapter kit available for use on existing wire installations (77280, power cable only)
- 5 Year Warranty (Control box 1 Year Warranty)


Control Box & Cable Options (sold separately)





Available Colors













Main Power Cable

& between halves 10' - 77270 20' - 77271 30' - 77272

40' - 77273

77504 Outdoor Rated

Switch Box

& Extension Cable

To be used with 77504

* All nart numbers listed are amber color Contact factory for custom request

All part numbers instea are umber color. Contact factory for custoff requests									
Available Models									
Part #	Vdc	Amps	# Modules per half	Number of Modules	Flash Patterns	Length	Height		
57818-1	12	2.1A	3	1	7	20"	12.5"		
57818-2	12	2.7A	3	2	7	20"	22"		
57818-3	12	3.3A	3	3	7	20"	30.5"		
57824-1	12	2.7A	4	1	7	26"	12.5"		
57824-2	12	3.3A	4	2	7	26"	22"		
57824-3	12	3.9A	4	3	7	26"	30.5"		
57830-1	12	3.3A	5	1	7	31.75"	12.5"		
57830-2	12	3.9A	5	2	7	31.75"	22"		
57830-3	12	4.5A	5	3	7	31.75"	30.5"		
57836-1	12	3.6A	6	1	7	37.5"	12.5"		
57836-2	12	4.2A	6	2	7	37.5"	22"		
57836-3	12	4.8A	6	3	7	37.5"	30.5"		

57000 SERIES TRAFFIC DIRECTORS

FLEET

57524



Features

- The hermetically sealed light-head will not be affected by outside factors such as temperature, humidity & condensation
- NO DOWN TIME heads are field replaceable in less than one minute!
- SWS pressure clip system ensure that no special tools are ever required
- A choice of control platforms cab-mounted slim-line control box or NEW outdoor rated switch box
- All electrical connections are made using the industry known, and trusted DTM series connections from TE
- 3 T-slots for unlimited mounting options (1/4" 20 hardware included)
- Adapter kit available for use on existing wire installations (77280, power cable only)
- 5 Year Warranty (Control box 1 Year Warranty)

Control Box & Cable Options (sold separately)







77504 Outdoor Rated **Switch Box**

Main Power Cable

To be used with 77501 20' - 77260


30' - 77261 40' - 77262 50' - 77263

Main Power Cable & Extension Cable To be used with 77504 & between halves 10' - 77270 20' - 77271

30' - 77272 40' - 77273

Dimensions





Available Colors



* All part numbers listed are amber color. Contact factory for custom requests

Available Models								
Part #	Vdc	Amps	# Modules per half	Flash Patterns	Length			
57524	12	2.4A	4	5	23.625"			
57530	12	3.0A	5	5	29.375"			
57536	12	3.6A	6	5	35.125"			
57542	12	4.2A	7	5	40.875"			
57548	12	4.8A	8	5	46.625"			

TRAFFIC ARROWS

In cab control box

- BatteryCheck™
- Manual Dim
- 10 Amp Auxiliary (definitions refer to page 2)

77501




Front



Features

- 12-24 Vdc operating range
- Double confirmation of button activation with a visual indicator LED and an internal audible buzzer
- BatteryCheck™ feature utilizes front mounted pattern matrix LEDs, to indicate the vehicles battery level
- Rugged compact design has a front tactile panel with indicator LEDs, an aluminum mounting bracket for above or below universal mounting options, and protected internal circuitry
- Included 10amp. auxiliary channel is independently controllable
- Has both a manual dimming option and cargo light control (for capable products)
- Quick disconnect wiring harness connection for fast installation
- 1 Year Warranty

Dimensions



Outdoor rated switch box


Features

- For use with Titan FLEET traffic arrows and traffic directors only.
- 12Vdc operating voltage.
- IP66 rated control box and 5-position switch, for externally mounting the control system
- Industry standard 4 patterns; Left, Right, Bar/ Warning, Center Out
- Supplied with a 12" min. power leads, and a connector harness for quick installation to the traffic directing device.
- Includes stainless steel mounting hardware
- 1 Year Warranty

Dimensions







TRAFFIC ARROWS

54000 Series

- 5 Year Warranty (5)
- AutoDim™



(definitions refer to page 2)



77501 Included with 54000

Main Power Cable

To be used with 77501 (sold separately) 20' - 77250

30' - 77251 40' - 77252 50' - 77253



77504 Outdoor Rated Switch Box

Included with 54002

Main Power Cable

To be used with 77504 (sold separately) 10' - 77270


20' - 77271

30' - 77272 40' - 77273

Features

- SAE J595 (2014) Class 1 & CA13 compliant lighthead
- MUTCD compliant
- The hermetically sealed light-head will not be affected by outside factors such as temperature, humidity & condensation
- UV stabilized, impact resistant ABS plastic body
- 15 high intensity modular heads with dual optic technology
- Cross Canada compliance with highway standards for BC, Ontario, New Brunswick, PEI, Nova Scotia, Newfoundland and Labrador
- Intelligent one wire communication for fast installation
- Standard traffic arrow patterns
- 5 Year Warranty (Control box 1 Year Warranty)
- Bracket mounting (98045) sold separately

Dimensions







Available Models									
Part #	Vdc	Mounting	Module Color	Amps	Lumens	# Patterns	Weight	Control Box / Switch	
54000	12	PM	Amber	5.25	4680 max	7	25lbs	77501	
54002	12	PM	Amber	5.25	4680 max	4	25lbs	77504	

