

NEW!

# 57000 SERIES TRAFFIC DIRECTORS FLEET PLUS

## TITAN SERIES

57436



- 5 Year Warranty
- AutoDim™
- 1 Wire Communication
- Cargo Lighting

(definitions refer to page 2)



### Features

- The hermetically sealed light-head will not be affected by outside factors such as temperature, humidity & condensation
- NO DOWN TIME – heads are field replaceable in less than one minute!
- SWS pressure clip system ensure that no special tools are ever required
- All electrical connections are made using the industry known and trusted DTM series connections from TE
- 3 T-slots for unlimited mounting options (1/4" - 20 hardware included)
- Stop turn kits available (96050)
- For factory installed Stop/Turn indicators, please add a -ST to your FLEETPLUS traffic director part number
- 5 Year Warranty (Control box 1 Year Warranty)





77501 (included)

**Main Power Cable**  
(sold separately)  
20' - 77265  
30' - 77266  
40' - 77267  
50' - 77268



### Dimensions



### Available Colors



\* All part numbers listed are amber color. Contact factory for custom requests

Available Models					
Part #	Vdc	Amps	Number of Modules	Flash Patterns	Length
57424	12	1.2A	4	5	23.625"
57430	12	1.5A	5	5	29.375"
✓ 57436	12	1.8A	6	5	35.125"
✓ 57442	12	2.1A	7	5	40.875"
✓ 57448	12	2.4A	8	5	46.625"
57454	12	2.7A	9	5	52.375"
57460	12	3A	10	5	58.125"
57466	12	3.3A	11	5	63.875"
57472	12	3.6A	12	5	69.625"

✓ = Top Seller

NEW!

# 57000 SERIES TRAFFIC DIRECTORS FLEET

## TITAN SERIES

57336



### Features

- The hermetically sealed light-head will not be affected by outside factors such as temperature, humidity & condensation
- NO DOWN TIME – heads are field replaceable in less than one minute!
- SWS pressure clip system ensure that no special tools are ever required
- A choice of control platforms – cab-mounted slim-line control box or NEW outdoor rated switch box
- All electrical connections are made using the industry known, and trusted DTM series connections from TE
- Adapter kit available for use on existing wire installations (77280)
- 3 T-slots for unlimited mounting options (1/4" - 20 hardware included)
- Stop turn kits available (96050)
- 5 Year Warranty (Control box 1 Year Warranty)

### Control Box & Cable Options (sold separately)



77501

**Main Power Cable**  
To be used with 77501  
20' - 77260  
30' - 77261  
40' - 77262  
50' - 77263




77504 Outdoor Rated Switch Box

**Main Power Cable**  
To be used with 77504  
10' - 77270  
20' - 77271  
30' - 77272  
40' - 77273



### Dimensions



### Available Colors



\* All part numbers listed are amber color. Contact factory for custom requests

Available Models					
Part #	Vdc	Amps	Number of Modules	Flash Patterns	Length
57324	12	1.2A	4	5	23.625"
57330	12	1.5A	5	5	29.375"
✓ 57336	12	1.8A	6	5	35.125"
✓ 57342	12	2.1A	7	5	40.875"
✓ 57348	12	2.4A	8	5	46.625"
57354	12	2.7A	9	5	52.375"
57360	12	3A	10	5	58.125"
57366	12	3.3A	11	5	63.875"
57372	12	3.6A	12	5	69.625"

✓ = Top Seller

**NEW!**

## 57000 SERIES SPLIT TRAFFIC ARROWS

FLEET  
**TITAN**  
SERIES

57824-1



(cable sold separately)

### Features

- The hermetically sealed light-head will not be affected by outside factors such as temperature, humidity & condensation
- NO DOWN TIME – heads are field replaceable in less than one minute!
- SWS pressure clip system ensure that no special tools are ever required
- A choice of control platforms – cab-mounted slim-line control box or NEW outdoor rated switch box
- All electrical connections are made using the industry known, and trusted DTM series connections from TE
- Adapter kit available for use on existing wire installations (77280, power cable only)
- **5 Year Warranty (Control box 1 Year Warranty)**

### Control Box & Cable Options (sold separately)



77501



**Main Power Cable**  
To be used with 77501  
20' - 77260  
30' - 77261  
40' - 77262  
50' - 77263



**77504 Outdoor Rated Switch Box**



**Main Power Cable & Extension Cable**  
To be used with 77504  
& between halves  
10' - 77270  
20' - 77271  
30' - 77272  
40' - 77273

### Available Colors



\* All part numbers listed are amber color. Contact factory for custom requests

Available Models							
Part #	Vdc	Amps	# Modules per half	Number of Modules	Flash Patterns	Length	Height
57818-1	12	2.1A	3	1	7	20"	12.5"
57818-2	12	2.7A	3	2	7	20"	22"
57818-3	12	3.3A	3	3	7	20"	30.5"
57824-1	12	2.7A	4	1	7	26"	12.5"
57824-2	12	3.3A	4	2	7	26"	22"
57824-3	12	3.9A	4	3	7	26"	30.5"
57830-1	12	3.3A	5	1	7	31.75"	12.5"
57830-2	12	3.9A	5	2	7	31.75"	22"
57830-3	12	4.5A	5	3	7	31.75"	30.5"
57836-1	12	3.6A	6	1	7	37.5"	12.5"
57836-2	12	4.2A	6	2	7	37.5"	22"
57836-3	12	4.8A	6	3	7	37.5"	30.5"

**NEW!**

## 57000 SERIES TRAFFIC DIRECTORS

FLEET  
**TITAN**  
SERIES

57524



(cable sold separately)

### Features

- The hermetically sealed light-head will not be affected by outside factors such as temperature, humidity & condensation
- NO DOWN TIME – heads are field replaceable in less than one minute!
- SWS pressure clip system ensure that no special tools are ever required
- A choice of control platforms – cab-mounted slim-line control box or NEW outdoor rated switch box
- All electrical connections are made using the industry known, and trusted DTM series connections from TE
- 3 T-slots for unlimited mounting options (1/4" - 20 hardware included)
- Adapter kit available for use on existing wire installations (77280, power cable only)
- **5 Year Warranty (Control box 1 Year Warranty)**

### Control Box & Cable Options (sold separately)



77501



**77504 Outdoor Rated Switch Box**

**Main Power Cable**  
To be used with 77501  
20' - 77260  
30' - 77261  
40' - 77262  
50' - 77263



**Main Power Cable & Extension Cable**  
To be used with 77504  
& between halves  
10' - 77270  
20' - 77271  
30' - 77272  
40' - 77273



### Available Colors



\* All part numbers listed are amber color. Contact factory for custom requests

Available Models					
Part #	Vdc	Amps	# Modules per half	Flash Patterns	Length
57524	12	2.4A	4	5	23.625"
57530	12	3.0A	5	5	29.375"
57536	12	3.6A	6	5	35.125"
57542	12	4.2A	7	5	40.875"
57548	12	4.8A	8	5	46.625"

### Dimensions

